Filed: October 29, 2001

Page 2 of 18

In the Claims:

1. (Canceled)

2. (Currently Amended) A positive electrode active material for secondary lithium and lithium-ion batteries comprising:

at least one electron conducting compound having the formula $LiM^1_{x-y}\{A\}_yO_z$ wherein M^1 is a transition metal; $\{A\}$ is represented by the formula Σw_iB_i wherein B_i is an element other than M^1 used to replace the transition metal M^1 and w_i is the fractional amount of element B_i in the total dopant combination such that $\Sigma w_i = 1$; B_i is a cation in $LiM^1_{x-y}\{A\}_yO_z$; $0.95 \le x \le 1.05$; $0 \le y \le x/2$; and $1.90 \le z \le 2.10$; and

at least one electron insulating and lithium ion conducting lithium metal oxide selected from the group consisting of LiAlO₂ and Li₂M 2 O₃, wherein M 2 is at least one tetravalent metal selected from the group consisting of Ti, Zr, Mn, Mo, Si, Ge, and Hf, Ru and Te.

- 3. (Original) The positive electrode active material according to Claim 2, wherein the lithium metal oxide is selected from the group consisting of Li₂TiO₃, Li₂ZrO₃ and mixtures thereof.
- 4. (Original) The positive electrode active material according to Claim 2, wherein the lithium metal oxide is Li₂TiO₃.
- 5. (Previously Presented) The positive electrode active material according to Claim 2, comprising from greater than or equal to 95% by weight and less than 100% by weight of $\text{LiM}^1_{x-y}\{A\}_yO_z$ and greater than 0% by weight and less than or equal to 5% by weight of the lithium metal oxide.

Filed: October 29, 2001

Page 3 of 18

- 6. (Currently Amended) The positive electrode active material according to Claim 2, wherein M¹ is selected from the group consisting of Co, Ni, Mn and Ti Fe.
- 7. (Previously Presented) The positive electrode active material according to Claim 2, wherein x=1 and z=2.
- 8. (Original) The positive electrode active material according to Claim 7, wherein M^1 is Ni.
- 9. (Original) The positive electrode active material according to Claim 7, wherein M^1 is Co.
- 10. (Previously Presented) The positive electrode active material according to Claim 2, wherein y > 0.
- 11. (Currently Amended) The positive electrode active material according to Claim 10, wherein the dopant elements B_i are selected from the group consisting of elements having a Pauling's electronegativity not greater than 2.05, Mo, Te and Ru.
- 12. (Original) The positive electrode active material according to Claim 10, wherein the dopant elements B_i include two or more dopant cations.
- 13. (Original) The positive electrode active material according to Claim 12, wherein the average oxidation state E of the dopant elements B_i , as determined using the formula $E = \sum w_i E_i$ wherein E_i is the oxidation state of dopant element B_i in the lithium metal oxide $LiM^1_{x-y}\{A\}_yO_z$, is represented by the relationship $2.5 \le E \le 3.5$.

Filed: October 29, 2001

Page 4 of 18

- 14. (Original) The positive electrode active material according to Claim 13, wherein $2.9 \le E \le 3.1$.
- 15. (Original) The positive electrode active material according to Claim 13, wherein E=3.
- 16. (Original) The positive electrode active material according to Claim 12, wherein at least one of the dopant elements B_i has a different oxidation state than M^1 in $LiM^1_{x-y}\{A\}_yO_z$.
- 17. (Original) The positive electrode active material according to Claim 12, wherein at least two of the dopant elements B_i have a different oxidation state than M^1 in $LiM^1_{x-y}\{A\}_yO_z$.
- 18. (Previously Presented) The positive electrode active material according to Claim 2, wherein x, y and z are values that provide a stable lithium metal oxide compound.
- 19. (Currently Amended) The positive electrode active material according to Claim 2, wherein the metal M^2 is present in $LiM^1_{x-y}\{A\}_yO_z$ as M^1 -or as a dopant element B_i or Al is present as a dopant element B_i .
- 20. (Original) The positive electrode active material according to Claim 19, wherein the lithium metal oxide has the formula $\text{Li}_2\text{M}^2\text{O}_3$ and M^2 includes Ti.
- 21. (Currently Amended) The positive electrode active material according to Claim 2, wherein M^1 is Ni or Co, M^2 is Ti, and the dopant elements B_i include Ti^{4+} -and Mg^{2+} .
- 22. (Original) The positive electrode active material according to Claim 21, wherein M¹ is Ni.

Filed: October 29, 2001

Page 5 of 18

- 23. (Withdrawn) The positive electrode active material according to Claim 22, wherein the dopant elements B_i further include Co^{3+} .
- 24. (Withdrawn) The positive electrode active material according to Claim 22, wherein the dopant elements B_i further include Li^+ cations.
- 25. (Withdrawn) The positive electrode active material according to Claim 2, wherein the $\text{LiM}^1_{x-y}\{A\}_yO_z$ compound has the formula $\text{LiNi}_{1-y}Co_aM^3_bM^4_cO_2$, wherein M^3 is selected from the group consisting of Ti, Zr, and combinations thereof; M^4 is selected from the group consisting of Mg, Ca, Sr, Ba, and combinations thereof; y=a+b+c, $0 < y \le 0.5$; 0 < a < 0.5; $0 < b \le 0.15$; and $0 < c \le 0.15$.
- 26. (Withdrawn) The positive electrode active material according to Claim 25, wherein $0.1 \le a \le 0.3$.
- 27. (Withdrawn) The positive electrode active material according to Claim 25, wherein M³ includes Ti.
- 28. (Withdrawn) The positive electrode active material according to Claim 27, wherein M⁴ includes Mg.
- 29. (Withdrawn) The positive electrode active material according to Claim 25, further comprising at least one metal oxide of the formula M^3O_2 .
- 30. (Withdrawn) The positive electrode active material according to Claim 29, wherein M³ includes Ti and said metal oxide is TiO₂.

Filed: October 29, 2001

Page 6 of 18

- 31. (Previously Presented) The positive electrode active material according to Claim 2, further comprising at least one electron insulating and lithium-ion conducting metal oxide.
- 32. (Previously Presented) The positive electrode active material according to Claim 31, wherein the metal oxide has the formula MO₂ wherein M is at least one tetravalent metal selected from the group consisting of Ti, Zr, Mo, Si, Ge, Hf, Ru and Te.
- 33. (Original) The positive electrode active material according to Claim 32, wherein $M=M^2$.
- 34. (Original) The positive electrode active material according to Claim 33, wherein said metal oxide is TiO₂.
- 35. (Previously Presented) A positive electrode for a secondary lithium or lithium-ion battery comprising the positive electrode active material of Claim 2, a carbonaceous material and a polymer binder.
- 36. (Previously Presented) A secondary lithium or lithium-ion battery comprising a positive electrode, a negative electrode and a nonaqueous electrolyte, wherein the positive electrode includes the positive electrode active material of Claim 2.
- 37. (Currently Amended) A positive electrode active material for secondary lithium and lithium-ion batteries comprising at least one compound of the formula $LiM^1_{x-y}\{A\}_yO_z$ and at least one lithium metal oxide selected from the group consisting of $LiAlO_2$ and of the formula $Li_2M^2O_3$, wherein M^1 is a transition metal, M^2 is at least one tetravalent metal selected from the group consisting of Ti, Zr, Mn, Mo, Si, Ge, Hf, Ru and Te, $\{A\}$ is represented by the formula Σw_iB_i wherein B_i is an element other than M^1 used to replace the transition metal M^1 and W_i is

Filed: October 29, 2001

Page 7 of 18

the fractional amount of element B_i in the total dopant combination such that $\Sigma w_i = 1$; B_i is a cation in $LiM^1_{x-y}\{A\}_yO_z; 0.95 \le x \le 2.10; 0 \le y \le x/2$; and $1.90 \le z \le 4.20$.

- 38. (Original) The positive electrode active material according to Claim 37, wherein the lithium metal oxide is selected from the group consisting of Li₂TiO₃, Li₂ZrO₃ and mixtures thereof.
- 39. (Original) The positive electrode active material according to Claim 38, wherein the lithium metal oxide is Li₂TiO₃.
- 40. (Original) The positive electrode active material according to Claim 37, comprising from greater than or equal to 95% by weight and less than 100% by weight of LiM¹_{x-y}{A}_yO_z and greater than 0% by weight and less than or equal to 5% by weight of the lithium metal oxide.
- 41. (Original) The positive electrode active material according to Claim 37, wherein x=1 and z=2.
- 42. (Original) The positive electrode active material according to Claim 37, wherein x=2 and z=4.
- 43. (Currently Amended) The positive electrode active material according to Claim 37, wherein M¹ is selected from Co, Ni, Mn, Ti, and Fe, Cr, V and Mo.
- 44. (Withdrawn) The positive electrode active material according to Claim 37, wherein M¹ is selected from Co, Ni, Mn and Ti.

Filed: October 29, 2001

Page 8 of 18

- 45. (Original) The positive electrode active material according to Claim 37, wherein y > 0.
- 46. (Currently Amended) The positive electrode active material according to Claim 45, wherein the dopant elements B_i are selected from the group consisting of elements having a Pauling's electronegativity not greater than 2.05, Mo, Te and Ru.
- 47. (Original) The positive electrode active material according to Claim 45, wherein the dopant elements B_i includes two or more dopant cations.
- 48. (Original) The positive electrode active material according to Claim 47, wherein the average oxidation state E of the dopant elements B_i , as determined using the formula $E = \sum w_i E_i$ wherein E_i is the oxidation state of dopant element B_i in the lithium metal oxide $LiM^1_{x-y}\{A\}_yO_z$, equals the oxidation state of the replaced transition metal ion $M^1\pm 0.5$.
- 49. (Original) The positive electrode active material according to Claim 48, wherein E equals the oxidation state of the replaced transition metal ion $M^1\pm0.1$.
- 50. (Original) The positive electrode active material according to Claim 48, wherein E equals the oxidation state of the replaced transition metal ion M^1 .
- 51. (Original) The positive electrode active material according to Claim 47, wherein at least one of the dopant elements B_i has a different oxidation state than M^1 in $LiM^1_{x-y}\{A\}_yO_z$.
- 52. (Original) The positive electrode active material according to Claim 47, wherein at least two of the dopant elements B_i have a different oxidation state than M^1 in $LiM^1_{x-y}\{A\}_yO_z$.

Filed: October 29, 2001

Page 9 of 18

- 53. (Original) The positive electrode active material according to Claim 37, wherein x, y and z are values that provide a stable lithium metal oxide compound.
- 54. (Withdrawn) The positive electrode active material according to Claim 37, wherein the metal M^2 is present in $LiM^1_{x-y}\{A\}_yO_z$ as M^1 or as a dopant element B_i , or Al is present as a dopant element B_i .
- 55. (Original) The positive electrode active material according to Claim 54, wherein the lithium metal oxide has the formula $\text{Li}_2\text{M}^2\text{O}_3$ and M^2 includes Ti.
- 56: (Original) The positive electrode active material according to Claim 37, further comprising at least one electron insulating and lithium ion conducting metal oxide.
- 57. (Previously Presented) The positive electrode active material according to Claim 56, wherein the metal oxide has the formula MO₂ wherein M is at least one tetravalent metal selected from the group consisting of Ti, Zr, Mo, Si, Ge, Hf, Ru and Te.
- 58. (Original) The positive electrode active material according to Claim 57, wherein M=M².
- 59. (Original) The positive electrode active material according to Claim 57, wherein said metal oxide is TiO₂.
- 60. (Original) A positive electrode for a secondary lithium or lithium-ion battery comprising the positive electrode active material of Claim 37, a carbonaceous material and a binder polymer.

In re Gao et al. Filed: October 29, 2001 Page 10 of 18

- 61. (Original) A secondary lithium or lithium-ion battery comprising a positive electrode, a negative electrode and a nonaqueous electrolyte, wherein the positive electrode includes the positive electrode active material of Claim 37.
- 62. (Currently Amended) A method of preparing a positive electrode active material for secondary lithium and lithium-ion batteries, the positive electrode active material including separate lithium metal oxide phases corresponding to the formulas LiM¹_{x-y}{A}_yO_z and Li₂M²O₃ or LiAlO₂, comprising the steps of:

intimately mixing source compounds containing M^1 , Li and optionally $\{A\}$ in amounts sufficient to provide a stoichiometric relationship between M^1 , Li and $\{A\}$ corresponding to the formula $\text{LiM}^1_{x-y}\{A\}_yO_z$ wherein M^1 is a transition metal, $\{A\}$ is represented by the formula Σw_iB_i wherein B_i is an element other than M^1 used to replace the transition metal M^1 and w_i is the fractional amount of element B_i in the total dopant combination such that $\Sigma w_i = 1$; B_i is a cation in $\text{LiM}^1_{x-y}\{A\}_yO_z$; at least one of M^1 and B_i is selected from the group consisting of Ti, Zr, Mn, Mo, Si, Al, Ge, Hf, Ru and Te; $0.95 \le x \le 2.10$; $0 \le y \le x/2$; and $1.90 \le z \le 4.20$;

firing the mixture in the presence of oxygen at an initial firing temperature and optionally one or more additional firing temperatures, at least one of said initial firing temperature and optionally one or more additional firing temperatures being the maximum firing temperature and at least one of said initial firing temperature and optionally one or more additional firing temperatures being between about 700°C and about 1000°C, wherein said firing step comprises heating the mixture at a sufficiently slow rate from 500°C to the maximum firing temperature to produce separate lithium metal oxide phases including LiM¹_{x-y}{A}_yO_z and LiAlO₂-or Li₂M²O₃₅ wherein M² is one of M¹ and B_i, and M² is selected from the group consisting of Ti, Zr, Mn, Mo, Si, Ge, Hf, Ru and Te; and

cooling the $\text{LiM}^1{}_{x\text{-}y}\{A\}_y O_z$ and $\text{Li}_2 M^2 O_3$ or LiAlO_2 compounds.

Filed: October 29, 2001

Page 11 of 18

- 63. (Original) The method according to Claim 62, wherein said firing step comprises heating the mixture from 500°C to the maximum firing temperature at an average rate of less than or equal to about 10°C/min.
- 64. (Currently Amended) The method according to Claim 62, wherein said firing step comprises heating the mixture at a sufficiently slow rate from 500°C to the maximum firing temperature to produce separate lithium metal oxide phases including LiM¹_{x-y}{A}_yO_z, Li₂M²O₃ and M²O₂, wherein one of M¹ and B_i is M² and M² is selected from the group consisting of Ti, Zr, Mo, Si, Ge, and Hf, Ru and Te.
- 65. (Withdrawn) The method according to Claim 64, wherein said mixing step comprises mixing source compounds wherein one of M^1 and B_i is selected from the group consisting of Ti and Zr.
- 66. (Withdrawn) The method according to Claim 65, wherein said mixing step comprises mixing source compounds wherein one of M^1 and B_i is Ti.
- 67. (Original) The method according to Claim 62, wherein said mixing step comprises dry mixing the source compounds.
- 68. (Original) The method according to Claim 62, wherein said mixing step comprises preparing a solution comprising M^1 and $\{A\}$ from source compounds comprising M^1 and $\{A\}$, precipitating the M^1 and $\{A\}$ out of solution to produce an intimately mixed hydroxide and blending the mixed hydroxide with a lithium source compound.
- 69. (Original) The method according to Claim 62, wherein said firing step comprises firing the mixture at a partial pressure of oxygen of at least 20 kPa.

Filed: October 29, 2001

Page 12 of 18

- 70. (Withdrawn) The method according to Claim 62, wherein one of M^1 and B_i is selected from the group consisting of Ti, Zr, Mn, Mo, Si, Ge, Hf, Ru and Te.
- 71. (Withdrawn) The method according to Claim 62, wherein said mixing step comprises mixing source compounds such that one of M¹ and B_i is Ti.
- 72. (Currently Amended) The method according to Claim 62, wherein said firing step comprises heating the mixture at a sufficiently slow rate from 500°C to the maximum firing temperature to produce separate lithium metal oxide phases including LiM¹_{x-y}{A}_yO_z and Li₂M²O₃ or LiAlO₂ such that the lithium metal oxide phases include greater than or equal to 95% by weight and less than 100% by weight of LiM¹_{x-y}{A}_yO_z and greater than 0% by weight and less than or equal to 5% by weight of Li₂M²O₃.
- 73. (Currently Amended) The method according to Claim 62, wherein said mixing step comprises mixing source compounds containing a transition metal M¹ selected from the group consisting of Co, Ni, Mn, Ti, and Fe, Cr, V and Mo.
- 74. (Withdrawn) The method according to Claim 62, wherein said mixing step comprises mixing source compounds containing a transition metal M¹ is selected from Co, Ni, Mn and Ti.
- 75. (Original) The method according to Claim 62, wherein said mixing step comprises mixing source compounds including dopant elements B_i such that y > 0.
- 76. (Currently Amended) The method according to Claim 75, wherein said mixing step comprises mixing source compounds including dopant elements B_i selected from the group consisting of elements having a Pauling's electronegativity not greater than 2.05, Mo, Te and Ru.

Filed: October 29, 2001

Page 13 of 18

- 77. (Original) The method according to Claim 75, wherein said mixing step comprises mixing source compounds including two or more dopant elements B_i
- 78. (Original) The method according to Claim 77, wherein said mixing step comprises mixing source compounds wherein the average oxidation state E of the dopant elements B_i , as determined using the formula $E = \sum w_i E_i$ wherein E_i is the oxidation state of dopant element B_i in the lithium metal oxide $\text{LiM}^1_{x-y}\{A\}_y O_z$, equals the oxidation state of the replaced transition metal ion $M^1 \pm 0.5$.
- 79. (Original) The method according to Claim 77, wherein said mixing step comprises mixing source compounds wherein the average oxidation state E of the dopant elements B_i , as determined using the formula $E = \sum w_i E_i$ wherein E_i is the oxidation state of dopant element B_i in the lithium metal oxide $\text{LiM}^1_{-x-y}\{A\}_y O_z$, equals the oxidation state of the replaced transition metal ion $M^1 \pm 0.1$.
- 80. (Original) The method according to Claim 77, wherein said mixing step comprises mixing source compounds wherein the average oxidation state E of the dopant elements B_i , as determined using the formula $E = \sum w_i E_i$ wherein E_i is the oxidation state of dopant element B_i in the lithium metal oxide $\text{LiM}^1_{x-y}\{A\}_y O_z$, equals the oxidation state of the replaced transition metal ion M^1 .
- 81. (Original) The method according to Claim 77, wherein said mixing step comprises mixing source compounds wherein at least one of the dopant elements B_i has a different oxidation state than M^1 in $LiM^1_{x-y}\{A\}_yO_z$.
- 82. (Original) The method according to Claim 77, wherein said mixing step comprises mixing source compounds wherein at least two of the dopant elements B_i has a different oxidation state than M^1 in $LiM^1_{x-y}\{A\}_yO_z$.

Filed: October 29, 2001

Page 14 of 18

- 83. (Original) The method according to Claim 77, wherein said mixing step comprises mixing source compounds in amounts sufficient to provide values for x, y and z that provide a stable metal oxide compound.
- 84. (Original) The method according to Claim 62, wherein said mixing step comprises mixing the source compounds in amounts sufficient to produce a $\text{LiM}^{1}_{x-y}\{A\}_{y}O_{z}$ compound wherein x=1 and z=2.
- 85. (Original) The method according to Claim 84, wherein said mixing step comprises mixing source compounds containing Ni or Co as the transition metal M¹.
- 86. (Currently Amended) The method according to Claim 85, wherein said mixing step comprises mixing source compounds containing Ti⁴⁺ and Mg²⁺ as <u>a</u> dopant <u>element</u> elements B_i.
- 87. (Original) The method according to Claim 86, wherein said mixing step comprises mixing source compounds containing Ni as the transition metal M^1 .
- 88. (Withdrawn) The method according to Claim 87, wherein said mixing step comprises mixing source compounds further including Co^{3+} as a dopant element B_i .
- 89. (Withdrawn) The method according to Claim 85, wherein said mixing step comprises mixing source compounds further including Li^+ as a dopant element B_{i} .
- 90. (Original) The method according to Claim 85, wherein said mixing step comprises mixing source compounds containing Co as the transition metal $M^{\rm l}$

Filed: October 29, 2001

Page 15 of 18

- 91. (Original) The method according to Claim 62, wherein said mixing step comprises mixing source compounds containing Li, Ni, Co, M^3 and M^4 in amounts sufficient to provide a stoichiometric relationship between Li, Ni, Co, M^3 and M^4 corresponding to the formula LiNi_{1-y}Co_a $M^3_bM^4_cO_2$ wherein M^3 is selected from the group consisting of Ti, Zr, and combinations thereof; M^4 is selected from the group consisting of Mg, Ca, Sr, Ba, and combinations thereof; M^2 is M^3 ; y=a+b+c, $0 < y \le 0.5$; 0 < a < 0.5; $0 < b \le 0.15$; and $0 < c \le 0.15$.
- 92. (Original) The method according to Claim 62, wherein said mixing step comprises mixing the source compounds in amounts sufficient to produce a $\text{LiM}^1_{x-y}\{A\}_yO_z$ compound wherein x=2 and z=4.
- 93. (Currently Amended) The method according to Claim 62, wherein said cooling step comprises cooling the $\text{LiM}^1_{x-y}\{A\}_yO_z$ and $\text{Li}_2M^2O_3$ or LiAlO_2 compounds at a rate of greater than or equal to about 0.5°C/min and less than or equal to about 140°C/min.
- 94. (Original) The method according to Claim 62, wherein said mixing step comprises mixing source compounds such that excess of the source compound containing lithium is provided in the mixture.
- 95. (Original) A method of preparing a positive electrode active material for secondary lithium and lithium-ion batteries, the positive electrode active material including separate lithium metal oxide phases corresponding to the formulas LiNi_{1-y}Co_aM³_bM⁴_cO₂ and Li₂M³O₃ comprising the steps of:

intimately mixing source compounds containing Li, Ni, Co, M^3 and M^4 in amounts sufficient to provide a stoichiometric relationship between Li, Ni, Co, M^3 and M^4 corresponding to the formula LiNi_{1-y}Co_a $M^3_bM^4_cO_2$ wherein M^3 is selected from the group consisting of Ti, Zr and combinations thereof; M^4 is selected from the group consisting of Mg, Ca, Sr, Ba, and combinations thereof; y=a+b+c, $0 < y \le 0.5$; 0 < a < 0.5; $0 < b \le 0.15$; and $0 < c \le 0.15$;

Filed: October 29, 2001

Page 16 of 18

firing the mixture in the presence of oxygen at an initial firing temperature and optionally one or more additional firing temperatures wherein at least one of the firing temperatures is the maximum firing temperature and wherein at least one of the firing temperatures is between about 700°C and about 1000°C, said firing step comprising heating the mixture from 500°C to the maximum firing temperature at an average rate of less than or equal to 10°C/min to produce separate lithium metal oxide phases including LiNi_{1-y}Co_aM³_bM⁴_cO₂ and Li₂M³O₃; and cooling the LiNi_{1-y}Co_aM³_bM⁴_cO₂ and Li₂M³O₃ compounds.

- 96. (Original) The method according to Claim 95, wherein said mixing step comprises mixing source compounds such that M³ includes Ti.
- 97. (Original) The method according to Claim 96, wherein said mixing step comprises mixing source compounds such that M⁴ includes Mg.
 - 98. (New) A positive electrode active material, comprising:

at least one electron conducting compound having the formula $LiM^1_{x-y}\{A\}_yO_z$ wherein M1 is a transition metal, $\{A\}$ is represented by the formula Σw_iB_i wherein B_i comprises at least one element having a Pauling's electronegativity not greater than 2.05 and w_i is the fractional amount of element B_i in the total dopant combination such that $\Sigma w_i = 1$, $0.95 \le x \le 1.05$, $0 \le y \le x/2$, and $1.90 \le z \le 2.10$; and

at least one electron insulating and lithium ion conducting lithium metal oxide of the formula $\text{Li}_2\text{M}^2\text{O}_3$, wherein M^2 is at least one tetravalent metal.